



NOTE  
 IF REMOTE(S) NOT USED A CONNECTOR MUST BE FITTED TO THE VACANT POSITION(S).  
 PINS 1, 2 AND 3 MUST BE LINKED ON THIS CONNECTOR.

HANDLE NORMALLY CLOSED CONTACT IS CONNECTED TO 2 PIN CONNECTOR ON MAIN PCB.  
 UNIT IS SHIPPED WITH A YELLOW SHORTING LINK ACROSS THIS CONNECTOR.  
 HANDLE INTERLOCK SWITCH MUST OPEN WHEN HANDLE IS REMOVED.  
 INTERLOCK VOLTAGE IS 24V DC.

<p>Hyperdrive Rail Ltd.        3 Station Road        Haverhill        Wiltshire        W16 1DD        United Kingdom        Tel: 01299 209 3651        Fax: 01299 209 3652        E-Mail: info@hyperdriverail.com</p>		<p>UNLESS OTHERWISE STATED ALL DIMENSIONS ARE IN MILLIMETRES        DIMENSIONS ARE GIVEN AS SHOWN UNLESS OTHERWISE SPECIFIED</p>		<p>DATE: 15.02.02        CHD</p>		<p>DRN: PJW</p>		<p>TITLE DETAIL:        VSC REMOTE WIRING        VARI-SPEED CONTROLLER        TWO REMOTE SYSTEM</p>	
<p>MOD: A        ISSUE SPEC: MATL:</p>		<p>SCALE: A2</p>		<p>APPD: NTS</p>		<p>DRG NO: 295027A</p>		<p>ISSUE: A</p>	